



MADE IN THE USA



ROTO-MILL



2551 320TH ST
Rock Valley, Iowa, 51247
712.476.BOSS (2677)
sales@herdbossfeeders.com

HERDBOSSFEEDERS.COM



ROTO-MILL

THE SPECS	RMC 12	RMC 24	RMC 36	RMC 48
ROLL WIDTH X DIAMETER	12" x 16" (30.5 cm x 41 cm)	24" x 16" (61 cm x 41 cm)	36" x 16" (91 cm x 41 cm)	48" x 16" (122 cm x 41 cm)
SHAFT DIAMETER	1 15/16" (5 cm)	1 15/16" (5 cm)	2 15/16" (8 cm)	2 15/16" (8 cm)
AUGER DISCHARGE	8" x 12' (20.3 cm x 3.7 m)	10" x 12' (25.4 cm x 3.7 m)	12" x 12' (30.5 cm x 3.7 m)	14" x 12' (35.6 cm x 3.7 m)
HYDRAULIC FEED AUGER	6" x 12' (15.2 cm x 3.7m)	8" x 10' (20.3 cm x 3 m)	12" x 10' (30.5 cm x 3 m)	12" x 10' (30.5 cm x 3 m)
HP REQUIREMENT	50	60	95	110

MAX. RATED DRY GRAIN CAPACITY (BUSHELS PER HOUR)				
BARLEY	300	600	900	1200
CORN	1250	2500	3750	5000
OATS	250	500	750	1000
WHEAT	500	1000	1500	2000

STANDARD FEATURES

- Chill cast rolls
- 16" roll diameter
- Grain flow control with magnetic grates
- Hydraulically driven hopper/pit auger
- Folding discharge auger
- Grain hopper folds up for easy serviceability and removal of rolls



OPTIONS

- Cuts per inch from 4-10 grooves per inch
- Intake/discharge augers
- Folding truck hopper that power rotates under the trailer with a pair of 12VDC drive motors
- Differential drive for additional processing of material

