



MADE IN THE USA



REEL MIXER TRUCK MOUNT



2551 320TH ST
Rock Valley, Iowa, 51247
712.476.BOSS (2677)
sales@herdbossfeeders.com

HERDBOSSFEEDERS.COM



REEL MIXER TRUCK MOUNT

THE SPECS	6150	6160	6175	6190
CAPACITY TOP OF STEEL	500 ft ³ (15 m ³)	600 ft ³ (17 m ³)	750 ft ³ (21 m ³)	900 ft ³ (26 m ³)
OVERALL LENGTH	206 in (5 m)	236 in (6 m)	255 in (7 m)	257 in (7 m)
MIXING CHAMBER LENGTH	168 in (4 m)	198 in (5 m)	210 in (5 m)	216 in (6 m)
FRONT DISCHARGE TO BUMPER	172 in (4 m)	208 in (5 m)	209 in (5 m)	209 in (5 m)
OVERALL HEIGHT	119 in (3 m)	119 in (3 m)	124 in (3 m)	130 in (3 m)
OVERALL WIDTH (MIXER ONLY)	102 in (3 m)	102 in (3 m)	107 in (3 m)	115 in (3 m)
WEIGHT EMPTY	13,400 lbs (6,078 kg)	17,600 lbs (7,983 kg)	22,500 lbs (10,206 kg)	23,500 lbs (10,659 kg)
MAXIMUM NET LOAD	15,000 lbs (6,804 kg)	18,000 lbs (8,165 kg)	22,500 lbs (10,206 kg)	27,000 lbs (12,247 kg)
FLIGHTING DIAMETER LOWER AUGER	24 in (61 cm)	24 in (61 cm)	24 in (61 cm)	26 in (66 cm)
FLIGHTING DIAMETER UPPER AUGER	22 in (56 cm)	22 in (56 cm)	24 in (61 cm)	26 in (66 cm)
HP REQUIREMENT	260	275	300	350

STANDARD FEATURES

- Direct reel drive with Nylatron® bearings
- Splined auger drive shafts
- Drop side for easier loading
- Bucket guards
- Bottom augers are 3/4" flights at the convergence area are supported by 1/2" or 3/4" tubes for long life
- Mixer drive has maintenance-free idlers
- Tsubaki® roller chain
- Oil bath enclosure
- Truck Mounts are designed to haul loads up to 30 lbs/ft³

OPTIONS

- Hydraulically controlled slide tray with magnets for simple feed placement
- Hydraulically powered, height adjustable auger discharge with magnets for applications needing more height or reach
- Knives for top auger for processing bulky ingredients
- Stainless steel liners
- Digi-Star®, Avery Weigh-Tronix®, and Point® scale systems

