



MADE IN THE USA



# V-SERIES MIXER



2551 320TH ST  
Rock Valley, Iowa, 51247  
712.476.BOSS (2677)  
sales@herdbossfeeders.com

**HERDBOSSFEEDERS.COM**



# V-SERIES MIXER

THE SPECS	810V	980V	1210V	1810V
CAPACITY W/ RUBBER EXT.	840 ft3 (23 m3)	1,020 ft3 (29 m3)	1,240 ft3 (35 m3)	1,830 ft3 (52 m3)
CAPACITY TOP OF TUB	706 ft3 (20 m3)	882 ft3 (25 m3)	1,094 ft3 (31 m3)	1,616 ft3 (46 m3)
LIGHT RATION CAPACITY	20,950 lbs	25,500 lbs	30,975 lbs	45,525 lbs
HEAVY RATION CAPACITY	29,330 lbs	35,700 lbs	43,365 lbs	63,735 lbs
WIDTH W/ FLIP-UP CONVEYOR	120 in (3 m)	120 in (3 m)	120 in (3 m)	120 in (3 m)
WIDTH W/O MAGNETIC TRAY	103 in (3 m)	103 in (3 m)	103 in (3 m)	103 in (3 m)
TUB WIDTH	103 in (3 m)	103 in (3 m)	103 in (3 m)	103 in (3 m)
OVERALL LENGTH	332 in (8 m)	336 in (9 m)	342 in (11 m)	450 in (11 m)
OVERALL HEIGHT W/ RUBBER EXT.	116 in (3 m)	129 in (3 m)	144 in (4 m)	138 in (4 m)
OVERALL HEIGHT TOP OF STEEL	106 in (3 m)	119 in (3 m)	134 in (3 m)	131 in (3 m)
OVERALL HEIGHT W/ DOOR BRACKET	119 in (3 m)	119 in (3 m)	n/a	n/a
WEIGHT EMPTY	22,800 lbs (10,342 kg)	23,500 lbs (10,659 kg)	25,400 lbs (11,521 kg)	34,500 lbs (15,649 kg)
FLOOR THICKNESS	3/4 in AR200 (19 mm)	3/4 in AR200 (19 mm)	3/4 in AR200 (19 mm)	3/4 in AR200 (19 mm)
WALL THICKNESS	3/8 in AR200 (10 mm)	3/8 in AR200 (10 mm)	3/8 in AR200 (10 mm)	3/8 in AR200 (10 mm)
AUGER FLIGHTS	3/4 in AR200 (19 mm)	3/4 in AR200 (19 mm)	3/4 in AR200 (19 mm)	3/4 in AR200 (19 mm)
SS CONVEYOR FLOOR	3/16 in SS (5 mm)	3/16 in SS (5 mm)	3/16 in SS (5 mm)	3/16 in SS (5 mm)
MINIMUM HP REQUIREMENTS	140	180	200	250

## STANDARD FEATURES

- 3/4" Abrasion Resistant (AR200) Steel Floor
- 3/8" AR200 Walls
- 3/8" AR400 Tub Baffles
- 3/4" Heavy Duty Construction Plate Frame
- 20-Ton Axles:
  - 32-Ton Tandem Spring Ride Suspensions
  - 45-Ton Tridum Spring Ride Suspension
- Super Single Tires 435/50R19.5
- All 1/4" Stainless Steel Conveyor
- Heavy Duty C188 Conveyor Chain
- Weighing Conveyor
- 6-Point or 8-point "Level Load" Weighing System By Digi-Star (Most Accurate in the Industry Vs. Hitch and Axle Weigh Bar)
- A Combination of Curved and Triangle Knives for Maximum Cutting Efficiency
- 77 Series Driveline

## OPTIONS

- Conveyors
  - Flat Dual
  - 3' Flip-Up
  - Fixed Sliding Dog Leg
- Stainless Steel Tub Liners
- Axles
  - Rear Steering
  - Hydraulic Brakes
- Hard Surface Weld Auger Edge
- Lugger Tires or Dual Tires
- Hydraulic Jack
- Comer 2-Speed Gearbox
- Zuidburg Powershift Transmission
  - Cooler and Can-bus Control System
- Interchangeable Parts: Several models have the same or interchangeable parts for simplified maintenance.
- Dual Magnet Tray System With Backstop
- Rear Commodity Door
- Bull Pull Hitch or Welded Clevis Hitch

